

AIR POLLUTION CONTROL PERMIT APPLICATION REQUIREMENTS

(Revised 7/1/01)

Operating Permits

**STATE OF VERMONT
Agency of Natural Resources
Department of Environmental Conservation
Air Pollution Control Division
Building Three South
103 South Main Street
Waterbury, Vermont 05671-0402**

**(802) 241-3840
FAX: (802) 241-2590**

<http://www.anr.state.vt.us/dec/air>

IMPORTANT - PLEASE READ BEFORE STARTING:

This outline is a general checklist of what constitutes the information necessary to submit an air pollution control operating permit application. **This outline is not a "fill-in-the-blanks" type form;** rather it is intended to give the applicant guidance as to what data the application needs to contain. This outline is intended to be used in conjunction with the Air Pollution Control Division's *Air Pollution Control Permitting Handbook* and the state of Vermont Air Pollution Control Regulations (*Regulations*). The Division's Engineering Section may be available to meet with an applicant to discuss the operating permitting process. Please contact the Division for more information.

Prior to submitting the prepared application, one company official responsible for its submission must read, complete and sign the attached form (page 6) certifying the information contained in the application is complete and accurate to the best of his/her knowledge and granting access to the property to verify information. This form **must** be incorporated as part of the submitted application.

There are no direct fees required to be submitted with an operating permit application.

A. Site Information

1. Name of the source; owner or parent corporation; and operator, if different. Please include the official corporation name as registered with the Secretary of State as well as any official tradenames.
2. Name, telephone and fax numbers and email (optional) of application contact(s).
3. Location and layout of source:
 - a. Physical location and mailing address, if different:
 - b. Attach maps, sketches and drawings showing:
 - i. A drawing which clearly shows the source's layout. Include building dimensions, location of equipment, location of exhaust stacks, etc. Include a north arrow.
 - ii. A drawing which clearly shows the buildings' side profiles in relation to stack locations, etc.. Include dimensions.
 - iii. A scaled engineering drawing describing the properties' plot plan. Identify all significant buildings, structures, other on-site uses, and roads. Include a north arrow, property boundaries, estimates of distances to property boundaries **and a description of adjacent land uses.**
 - iv. A U.S.G.S. topographical, town, or highway map depicting the source's location.

B. Operational Information

1. Nature of Operation:

- a. Please provide a narrative description of the facility operations. Be sure to identify and include all individual processes or operations at the facility that may generate air pollution. Some common examples include combustion units (boilers, furnaces, diesel engines, waste oil furnaces, outdoor wood stoves but not motorized vehicles), occasional open burning, dust producing operations (woodworking operations including transfer and disposal of wood wastes, sandblasting, aggregate and other dust producing material handling, processing or transfer operations), solvent degreasing operations, painting and coating operations, printing operations, other evaporative operations or sources of fumes, potential odor producing operations, and volatile organic liquid storage tanks including fuel storage tanks.
- b. Please sketch a process flow diagram with arrows depicting emissions to the atmosphere.
- c. For multiple processes using common vents or stacks, please provide an additional sketch of the exhaust system(s) indicating the location of inlets and approximate distances, dimensions, and flow rates.
- d. Please provide the facilities' SIC code(s).

2. Equipment Specifications:

- a. Please provide specifications and/or copies of manufacturer's literature for process equipment including maximum design and actual process rates and capacities (**see Attachment A**). For volatile organic liquid storage tanks including fuel storage tanks, please indicate whether it is above ground or below ground, the date of installation, the size in gallons or cubic meters, the fuel or product stored, and the maximum true vapor pressure of the product if known.
- b. Please provide the date of installation of the piece of equipment.
- c. Please provide specifications and/or copies of manufacture's literature for air pollution control equipment (**see Attachment B**).
- d. Please provide the following parameters for each vent or stack, if known:
 - i. Outlet Height
 - ii. Internal Diameter
 - iii. Flow Rate: actual cubic feet per minute & dry standard cubic feet per minute
 - iv. Moisture Content of Exhaust Gas (% by volume)
 - v. Exhaust Gas Temperature at Outlet
 - vi. Velocity at Outlet: feet per second
 - vii. Static Pressure, if known: inches of water
 - viii. Lack or Presence of A Rain Cap On The Stack.

3. Existing or Proposed Operating Limits

- a. Annual fuel caps, fuel types, fuel sulfur content (% by weight)
- b. Hourly operation (must be enforceable e.g., non-resettable meters installed, etc.)
- c. Raw material throughput or final product output caps
- d. Solvent or coating usage
- e. If applicable, existing permit limits

C. Quantification of Air Contaminant Emissions

Methods of estimating and quantifying emissions are described in Appendix L of the Division's *Air Pollution Control Permitting Handbook*. Please include fugitive emissions (dust, vapors, etc.). Attach all sample calculations and assumptions as an Appendix to the application. To assist applicants, the U.S. EPA compiles emission factors for most common air pollution generating equipment and operations in A Compilation of Air Pollution Emission Factors (AP-42). These emission factors are available at the U.S. EPA internet site <http://www.epa.gov/ttn/chief>

Step 1. Emissions Inventory

For each process or piece of equipment at the facility, please estimate the *allowable* emissions of all regulated contaminants. Consult Appendix C of the *Regulations* for a list of regulated hazardous contaminants. All estimates of allowable emissions should be calculated assuming the processes and equipment are operated at their **maximum** capacity and at continuous operation (8760 hours per year), unless the applicant has proposed to limit the operation, in section C(5).

For sources which operate under restrictions of an existing air pollution control permit, state or federal standard, or other limiting regulation, the applicant should consider that restriction to be the allowable emission rate for the affected process, unless the applicant proposes a change. Please include the date that the equipment was, or will be installed. **Installation dates are significant in the permitting process.**

If a control device is installed or proposed, an estimate of emissions *after control*, based on the control efficiency of the device, should also be included. Control efficiency documentation must be attached as an Appendix to the submitted application.

In similar fashion, also include an estimate of the *actual emissions* from each process or piece of equipment at the facility based on actual operating hours and rates averaged over the last two years. List all assumptions and sample calculations and attach these as an Appendix. The following format is suggested:

Process Name:			Date of Installation:				
Contaminant	Uncontrolled or Allowable Emissions (lb/hr) & (ton/yr)		Type of Control Device & Control Efficiency	Allowable Emissions After Control (lb/hr) & (ton/yr)		Actual Emissions (lb/hr) & (ton/yr)	
sulfur dioxide (SO ₂)							
oxides of nitrogen (NO _x)							
particulate matter (TSP & PM ₁₀)							
lead (Pb)							
carbon monoxide (CO)							
volatile organic compounds (VOC)							
(hazardous chemical)							
(hazardous chemical)							
(hazardous chemical)							

(NOTE: Hazardous chemicals that are designated as VOC's should also be added in with the VOC compounds)

Step 2. FACILITY TOTALS

Once emissions from all processes at the facility have been inventoried they should be totaled and summarized:

Entire Facility Summary: SAMPLE FORMAT		
CONTAMINANT	TOTAL ALLOWABLE EMISSIONS FROM FACILITY (ton/year)	ESTIMATED ACTUAL EMISSIONS FROM FACILITY (ton/year)
sulfur dioxide (SO ₂)		
oxides of nitrogen (NO _x)		
particulate matter (TSP & PM ₁₀)		
lead (Pb)		
carbon Monoxide (CO)		
volatile organic compounds (VOC)		
hazardous air contaminant		
hazardous air contaminant		
hazardous air contaminant		
Total		

Step 3. IDENTIFY APPLICABLE REQUIREMENTS & CERTIFY COMPLIANCE

To assess the compliance status of the existing facility, the applicant is required to review each section of the *Regulations* and any applicable Federal New Source Performance Standard (NSPS) or National Emission Standard for Hazardous Air Pollutants (NESHAP) found in Title 40 of the *Code of Federal Regulations* Parts 60, 61 and 63. The applicant must then certify whether the facility is currently operating (or will be operated) in compliance with each applicable section. This review must include toxic air emissions as described in section 5-261 of the *Regulations*.


If applicable, the applicant is further required to evaluate the source's compliance status with the conditions contained in the facility's current Air Pollution Control Permits and certify that it is currently operating in compliance with its permits. The applicant is also required to certify that all of the equipment on the property has been properly permitted in the past. That is to say, that **any equipment installed since 1979 without a permit must fulfill obligations under Subchapter V - Review of New Air Contaminant Sources, found in the Regulations.**

The applicant is required to state the method (e.g. stack test, restrictions, etc.) or assumptions that were used to determine the compliance status with each regulation or permit condition. The applicant is further required to state or specify a method to insure that compliance is adhered to in the future.

If the facility is not operating in compliance, then applicants must develop and submit a plan which identifies how it intends to achieve compliance. The plan must include a schedule of milestones leading to compliance. The applicant will be required to submit progress reports upon achieving each milestone or every six months. This is known as the "source's compliance plan."

Step 4. PUBLIC COMMENT

This section applies to all sources applying for an operating permit. Vermont Statute requires the Division to post notice of receipt of an administratively complete operating permit application in a local newspaper. This notice will indicate the location where a copy of the permit application may be reviewed by members of the public. In addition, the Division is required to post notice of all proposed final decisions and allow 30 days for the public to comment and request an informational meeting to be scheduled. If an informational meeting is requested, the Division will post notice which will include the time and location of the informational meeting. The Division will hold open the public comment period for one week after the informational meeting. The Division is then allowed time to respond to public comment. If the source is subject to federal review, more time may be allotted. **Three copies of the application must be submitted** to the Division.



CERTIFICATION OF INFORMATION ACCURACY

I certify under penalty of law that I have personally examined and am familiar with the information submitted herein. Based on information and belief formed after reasonable inquiry, the submitted information is true, accurate and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment.

(Signature)

(Date)

(Print Name)

(Title)

CONSENT FOR ACCESS TO PROPERTY

I recognize that by signing this application, I am giving consent to employees of the State of Vermont to enter the subject property for the purpose of obtaining information relevant to the processing of this application. I also understand that by acceptance of a Permit, I agree to allow representatives of the State of Vermont access to the properties covered by the Permit, at reasonable times, for the purpose of ascertaining compliance with the Permit and with Vermont environmental and health statutes and regulations.

(Signature)

(Date)

(Print Name)

(Title)

THIS PAGE LEFT BLANK

ATTACHMENT A

ADDITIONAL DATA NEEDED FOR SPECIFIC SOURCE CATEGORIES

Listed below are examples of some specific informational requirements for typical source categories. Some air contaminant sources may generate emissions from more than one of the below listed source categories at the same site. Therefore, please review all the categories in order to ensure all required information has been provided. If a category is not included, please consult the Division for further guidance.

BOILERS

Boiler Manufacturer, Model No., Serial No., Date of Manufacture
Date of Installation
Purpose of boiler: steam or hot water production?
 process heat or electric generation?
Boiler Type: (e.g., water-tube, fire-tube, sectional)
Boiler Maximum Rated Heat Input: (million British Thermal Units per hour - MMBtu/hr)
Boiler Maximum Rated Heat Output: (horsepower)
Boiler Design Heat Transfer Efficiency (i.e., MMBtu/hr output divided by MMBtu/hr input)
Firebox Heating Surface Area and Volume (esp. for solid fuel-fired boilers)
Maximum & Design Operating Pressures (psig)
If purpose of the boiler is for steam production, indicate maximum and design steam production rate (lbs of steam/hr)
Fuel Type: primary & secondary
Assumed Fuel Higher Heating Values: liquid (MMBtu/gal); solid (MMBtu/dry ton); gaseous (Btu/cubic foot):
Fuel Sulfur Content (% by weight, dry):
If solid fuel, indicate ash content (% by weight, dry) and fuel moisture content (% by weight):
Will fly ash collection/reinjection be used? If so, provide specifications on this equipment.
Number of Burners
Burner Manufacturer, Model No., Serial Nos. (if available)
Burner Type or Fuel Feeding Mechanism
Maximum Fuel Firing Rate: liquid fuel (gal/hr); solid fuel (tons/hr); gaseous fuel (cubic feet/hour)
If oil-fired, indicate method of atomization (steam or compressed air)
Forced draft or atmospheric boiler
Combustion air blower capacity in actual cubic feet per minute (if applicable)
Excess Air (% by volume)
Carbon Dioxide (CO₂) Content of the Flue Gas (% by volume, wet)
Moisture Content of the Flue Gas (% by volume)
Will flue gas recirculation (FGR) be employed?
Will staged air combustion or staged fuel combustion be used?
Will the combustion air be preheated?
Will low-Nox burners be utilized? If so, what type:(staged air combustion, staged fuel combustion, internal flue gas recirculation, external flue gas recirculation, or ceramic radiant combustion)?
Sootblowing frequency and duration
Will the steam be utilized for electrical generation? If so, provide specifications on the generating capacity.

INTERNAL COMBUSTION ENGINES

Engine Manufacturer, Model No., Serial No. (if available), Date of Manufacture
Date of Installation:
Engine Use (emergency backup, primary power, peaking power, nongenerator use (explain)):
Engine Rating (Horsepower):
Engine Rating (Continuous/Prime/Standby):
Generator Rating (kW):
Engine Operating Speed (rpm):
Fuel Type (on-highway diesel [clear, no tint]/standard diesel [red tint]/natural gas/propane/gasoline/other):
Maximum Fuel Firing Rate @ 100% load (liquid fuel [gals/hr]/gaseous fuel [cubic feet/hr]):
Engine Design: number of cylinders
displacement per cylinder (cubic inches)
two-cycle or four-cycle
turbocharged, supercharged or naturally aspirated?
intercooled or aftercooled?
method of ignition [spark or compression (diesel cycle)]:
Is the engine certified to meet the federal nonroad engine emission limits of 40 CFR Part 89?
If so, state engine certification year (ie. the year of the standards to which it is certified):
Will stratified charge or engine retard be utilized?
Will the engine utilize a catalyst for air pollution control?
Will the engine be equipped with a smoke particle trap to reduce emissions of particulate matter?
Generator Manufacturer, Model No., Serial No. (if available)
Generator Rating (KW): Prime power and/or Stand-by power
Exhaust Chemistry (if available)

MUNICIPAL SOLID WASTE AND MEDICAL WASTE INCINERATORS

Incinerator Manufacturer, Model No., Serial No. (if available), Date of Manufacture
Date of Installation:
Maximum design charging rate (tons per hour and tons per day):
Type of Furnace Design (Mass Burn, RDF, etc.):
Continuous or Batch system, if continuous please indicate specifications on feeding mechanism and on grate system, if batch please indicate cycle time
Number combustion chambers, their respective min. & max. operating temperatures (°F) and residence times (seconds)
Explanation of the combustion control system - oxygen trim, recycling of flue gas, overfire air, and underfire air system
Characteristics of waste stream
Description of materials separation program
Number of Auxiliary Burners
Per Burner - type of fuel, fuel sulfur content (% by weight), fuel higher heating value
- burner maximum heat input rating (MMBtu/hr)
Method of ash removal and disposal; please indicate techniques to be used to avoid fugitive emissions of ash
Measures to be taken in order to avoid nuisance dust and odors
Will heat recovery be utilized? If yes, provide the following information on the heat recovery unit:
Manufacturer, Model No., Serial No. (if available)
Rated Heat Input (MMBtu/hr), Rated Output (HP)
If steam will be generated, maximum steam production and pressure (lbs. of steam/hour and psig)
Will electricity be generated? If so, provided the following:
Generator Manufacturer, Model No., Serial No. (if available)
Maximum Generating Capacity (KW)
Maximum Exhaust Air Flow - actual cubic feet per minute
- dry standard cubic feet per minute
Exhaust Moisture Content (% by volume)
Exhaust Carbon Dioxide (% by volume, wet)

SMALL PATHOLOGICAL AND CREMATORY INCINERATORS

Incinerator Manufacturer, Incinerator Model No., Incinerator Serial No., Date of Manufacture
Date of Installation:
Maximum Charge Weight (lbs):
Maximum Charge Rate (lbs/hr):
Method of Loading (batch/continuous/other):
If batch, cycle time for full charge (minutes):
Type and characteristics of waste to be incinerated: [e.g., Classification (i.e., Type O), Btu Content, Plastics Content, Moisture Content, etc.]
Number of Combustion Chambers:
Per Chamber: type of auxiliary fuel, fuel sulfur content (% by weight), fuel higher heating value
 auxiliary burner maximum heat input (MMBtu/hr):
 minimum and maximum operating temperatures (°F):
 minimum residence time (seconds) @ 1600 °F:
Exhaust Air Flow: actual cubic feet per minute:
 dry standard cubic feet per minute:
Exhaust Moisture Content (% by volume):
Exhaust Carbon Dioxide, CO₂ Content (% by volume, wet):

STORAGE TANKS

Storage Tank Manufacturer, Serial No., Date of Manufacture (required for determining applicability of federal NSPS Subpart Kb 40CFR§60.110b)
Date of Installation:
Type of Storage Vessel (fixed roof, internal floating roof, external floating roof, pressure vessel, other):
If pressure vessel, what is the operating pressure (psi)?:
Design Capacity of storage tank (gallons):
Working Capacity of storage tank (gallons):
Estimated Annual Throughput (gallons):
Storage tank dimensions:
Type of liquid stored: (e.g. gasoline, No.2 fuel oil, asphalt (specify), chemical (specify), etc.)
Temperature of Liquid Stored (°F): (e.g. only if liquid is heated or cooled to maintain a certain temperature such as asphalt cement or No. 6 fuel oil)
Maximum True Vapor Pressure of Liquid Stored (psi):
Is the Storage Tank Above Ground or Below Ground?
If above ground, is it located outside or within a climate controlled building?
Color of tank:
Is the tank equipped with pressure/vacuum relief vents? If so, how many are there and are they atmospheric vents (ie. unrestricted flow) or pressure/vacuum relief valves? If there are atmospheric vents what size are the openings? If there are **pressure** relief valves, what is the design opening pressure (psi) and the manufacturer's tolerance (+/-)? If there are **vacuum** relief valves, what is the design opening vacuum pressure (psi) and the manufacturer's tolerance (+/-)? Do all pressure/vacuum relief valves remain functional after popping or do they need immediate replacement?
Is vapor balance or vapor recovery used during filling or emptying of the tank (specify):
If equipped with a floating roof;
 Describe the primary seal type (metallic shoe, liquid-mounted resilient filled seal, vapor-mounted resilient filled seal, flexible wiper seal
 Describe the secondary seal type:
 Welded deck or bolted deck?
 Number of fixed roof support columns, dimensions and controls (e.g. gasket, flexible fabric seal, other):
 Number of deck fittings, types (e.g. columns, access hatches, deck drains, stub drains, rim vents, ladder wells, other) and controls (e.g. gaskets, fabric seals, sliding cover, other):

NON-METALLIC MINERAL PROCESSING

Type of non-metallic mineral(s) to be processed: (e.g. sand, gravel, ledge rock, granite, marble, talc ore, etc.)

Will the gravel material (if applicable) be prescreened prior to crushing?

Method of quarrying material:

Include a process flow diagram depicting each piece of equipment, process flow, and anticipated processing rates (tph) input to each piece of equipment, include recirculation load if applicable:

Number of crushers to be utilized:

Per Crusher - crusher manufacturer, model no., serial no., date of manufacture (required for determining applicability of federal NSPS Subpart OOO 40CFR§60.670)

- type of crusher: (e.g., jaw, cone, etc.)
- manufacturer's maximum rated capacity at largest possible setting (specify setting) (tph):
- manufacturer's maximum rated capacity at proposed setting (specify setting) (tph):
- actual anticipated capacity at the proposed setting, include recirculation load if applicable (tph):

Number of screening units to be utilized:

Per Screen Unit - screening unit manufacturer, model no., serial no., date of manufacture (required for determining applicability of federal NSPS Subpart OOO 40CFR§60.670)

- number of screens:
- dimensions of screens (ft.):
- size distribution of the products:
- manufacturer's rated capacity (tph):
- actual anticipated capacity, include recirculation load if applicable (tph):

Number of belt conveyors:

Per conveyor - conveyor manufacturer, model no., conveyor serial no., date of manufacture (required for determining applicability of federal NSPS Subpart OOO 40CFR§60.670)

- length and width of conveyor:
- enclosed or not enclosed:
- manufacturer's rated capacity (tph):
- actual anticipated capacity, include recirculation load if applicable (tph):

Non-metallic mineral moisture content (% by weight):

Will a fabric filter (baghouse) dust collector be used to control fugitive dust from the processing equipment?

If so, describe methods to be used to capture and control the fugitive dust: (e.g. location of dust collection pickup points; describe dust collection pickup points; estimate of capture efficiency at each pickup point; air flow rates at pickup points; dust collector specifications (see Attachment B).

Will wet suppression be utilized to control fugitive dust from the processing equipment?

If so, describe methods and equipment to be used to control the fugitive dust: (e.g., specify location, make and model of water spray nozzles; type of nozzles (e.g. fog, saturation, etc.); water pressure and flow rates; source of water (e.g. municipal water; dug well; artesian well; on-site surface water source such as pond, quarry or river; off-site source)

On an attached flow diagram of the processing equipment, please note the location of all control devices (enclosures, dust pickup points, water nozzles, pressure gauges, source of water, pump locations, etc.).

HOT MIX ASPHALT PLANTS

Plant Manufacturer, Model No., Date of manufacture

Date of Installation

What type of HMA plant (batch or drum-mix):

If batch plant, maximum Batch Size (tons)

If drum mix, where will the asphalt cement (AC) be mixed with the hot aggregate material; if material will be mixed outside the drum please indicate method and equipment; if AC will be injected into drum please indicate the location of the injection point

Maximum Production Rate (tons per hour):

Actual Design Production Rate (tons per hour):

Rotary Dryer Dimensions:

Asphalt cement type: (include Material Safety Data Sheet)

Number of storage tanks and capacity for asphalt cement:

Number of storage tanks and capacity for fuel:

Rotary Dryer Burner Type:

Fuel Type:

Sulfur Content (% by weight) :

Fuel Higher Heating Value - liquid fuel (MMBtu/gallon)

- gaseous fuel (Btu/cubic foot)

Rotary Dryer Burner Maximum Rated Heat Input (MMBtu/hr)

Rotary Dryer Burner Maximum Fuel Firing Rate - liquid fuel (gallons/hour)

- gaseous fuel (cubic feet/hour)

Will a storage silo be utilized? If so, identify manufacturer, model no., serial no., capacity, and size

Number of feed hoppers

For each feed hopper: manufacturer, model no., serial no., material contents (e.g., 3/8" stone, sand, etc.),

capacity (cubic yards), feed rate (tons per hour)

Number of conveyors (including bucket elevators)

For each conveyor: manufacturer, model no., serial no., transfer rate (tons/hour), enclosed or not enclosed, vented to a fabric filter?

Number of weight hoppers

For each weight hopper: manufacturer, model no., serial no., transfer rate, enclosed or not enclosed, vented to a fabric filter?

Number of screening units

For each screening unit: manufacturer, model no., serial no., production rate (tons per hour), enclosed or not enclosed, vented to a fabric filter?

Baghouse fines removal procedures and method of final disposal

If an internal combustion engine will be utilized to generate electricity on-site please supply specifications in accordance with the above requirements. Likewise for fugitive emission points.

FLUID EVAPORATORS

Manufacturer, Model No., Serial No. Date of Manufacture

Date of Installation:

Burner Maximum Rated Heat Input (MMBtu/hr)

Fuel Type, maximum sulfur content (% by weight), fuel higher heating value

Maximum fuel consumption rate (gallons/hour)

Maximum processing rate (gallons/hour)

Number of solutions to be processed

Per solution processed: manufacturer, product name, list of all constituents contained in the product, percentage of each constituent in the product (% by weight or volume, please specify), product density (lbs/gallon), maximum processing rate (gallons/hour), volatile organic compound content (% VOCs by volume)

System exhaust rate - actual cubic feet per minute

CONCRETE BATCHING OPERATIONS

Batch Plant Manufacturer, Model, Date of Manufacture

Date of Installation:

Maximum Production Rate (tons per hour of concrete)

Number of Cement Storage Silos

For each Cement Silo: manufacturer, model no., serial no., capacity (cubic yards of cement), control device, specifications on pneumatic cement transfer system (e.g., pressure, transfer rate, etc.), length of time for unloading cycle (minutes)

Number of feed hoppers

For each feed hopper: manufacturer, model no., serial no., material contents (e.g., 3/8" stone, sand, etc.), capacity (cubic yards), feed rate (tons per hour)

Number of conveyors (including bucket elevator)

For each conveyor: manufacturer, model no., serial no., transfer rate (tons/hour), enclosed or not enclosed, vented to a fabric filter?

Will weigh hoppers or constant weight feeders be utilized?

Number of weigh hoppers or weight feeders

For each weigh hopper or weight feeder: manufacturer, model no., serial no., transfer rate (tons/hour), enclosed or not enclosed, vented to a fabric filter?

What means of dust control will be utilized to minimize emission during truck loading?

What portions of the batch plant will be enclosed if any?

Will fuel burning equipment be utilized on-site? If so, please provide the following: maximum rated heating input (MMBtu/hr), maximum fuel firing rate (gallons per hour, cubic feet per hour, etc.), fuel type, fuel maximum sulfur content, and fuel higher heating value (MMBtu/gallon, Btu/cubic foot, etc.).

Will an internal combustion engine be utilized to generate electricity on-site? If so, please provide the information identified above.

SPRAY BOOTHS

Manufacturer, Model No.

Date of Installation

Spray Booth Type (dry filter, water wash, etc.)

Spray Booth Outside Dimensions (width, length, and height)

Method of Coating Application: (air atomization spray, airless spray, air assisted airless spray, electrostatic/air atomization, electrostatic/airless, electrostatic/air assisted airless, High Volume Low Pressure spray)

Number of exhaust fans and maximum air flow rating for each fan

Number and dimensions of exhaust filter elements (width, height and thickness of each element)

Capture efficiency of the filter elements for a specific particle size

Will ovens or heaters be utilized to speed curing of applied product?

Estimate of transfer efficiency

Filter face velocity (feet per minute)

Describe how pieces are placed and removed

For each coating or solution to be applied: manufacturer, product name, list of all constituents contained in the product, percentage of each constituent in the product (% by weight or volume, please specify), product density (lbs/gallon), usage rate (gallons per hour), volatile organic compound content (% VOCs as applied, excluding water) Clean up solvents (same as listed for coatings)

COMBUSTION TURBINES

Manufacturer, Model No., Serial No., Date of Manufacture
Date of Installation
Type of Combustion Turbine
Peaking Unit or Combined-Cycle
Combustion Turbine Size
Fuel Type
Maximum Fuel Sulfur Content (% by weight)
Fuel Higher Heating Value- liquid fuel (MMBtu/gal); gaseous fuel (MMBtu/cubic foot)
Fuel Lower Heating Value- liquid fuel (MMBtu/gal); gaseous fuel (MMBtu/cubic foot)
Combustion Turbine Rated Heat Input, MMBtu/hr, (based on HHV of fuel and LHV of fuel)
Combustion Turbine Generating Capacity (MW)
If heat recovery will be utilized provide the following:
Heat Recovery Steam Generator Inlet and Outlet Temperatures (°F)
Steam Production Rate and pressure (lbs of steam per hour and psig)
Steam Turbine Electric Generating Capacity (MW)
Will steam or water be injected into the combustion turbine, if so, please specify water to fuel ratio

FUGITIVE SOURCES

Type of fugitive emission point: (open door or window, haul road, aggregate pile, bucket loading of material, truck dumping, etc.)
Average material moisture content (aggregate, road, etc.)
Measures to be employed to reduce emissions (wet suppression, chloride application, wetting followed by sweeping of Paved portions, maintaining negative pressures within a room or building, etc.)

COATING OPERATIONS (other than spray booths and lithographic printing)

Type of coating process (silkscreen, curtain coating, web, etc.)
Date of Installation
Substrate material
Equipment Manufacturer, Model No., Serial No. (if available)
Number of ovens
Type of oven (flame, electric, ultraviolet, or infra-red)
For each oven: manufacturer, model no., serial no., fuel type, maximum sulfur content (% by weight), fuel higher heating value), no. of burners/oven (or heat lamps) and their respective maximum rated heat inputs (MMBtu/hr), exhaust air flow (acfm)
For product applied and wash solution: manufacturer, product name, list of all constituents contained in the product, percentage of each constituent in the product (% by weight or volume, please specify), product density (lbs/gallon), maximum usage rate (gallons per hour), volatile organic compound content (% VOCs by volume as applied, excluding water)

LITHOGRAPHIC PRINTING OPERATIONS

Manufacturer, Model No., Serial No., Date of Manufacture

Date of Installation

Type of printing process, relief (i.e., letterpress), planographic (i.e., lithographic), intaglio (i.e., rotogravure), stencil (i.e., screen), sheetfed or web fed, maximum paper size, cold-set or heatset? If heatset, provide the following:

Number of ovens

Type of oven (flame, electric, ultraviolet, or infra-red)

Per Oven: manufacturer, model no., serial no., fuel type, maximum sulfur content (% by weight),

fuel higher heating value, no. of burners/oven (or heat lamps) and their respective maximum rated heat inputs

(MMBtu/hr), exhaust air flow (acfm)

Will chill rollers be required?

Number of ink fountains and ink rollers

Number of fountain rollers

Number of colors to be applied

For each ink product, fountain solution, and wash solution: manufacturer, product name, list of all constituents

contained in the product, percentage of each constituent in the product (% by weight or volume, please specify),

product density (lbs/gallon), maximum usage rate (gallons per hour), volatile organic compound content (% VOCs by

volume as applied, excluding water)

Other solvents (same as listed for ink products, etc.)

PLASTIC EXTRUSION PROCESSES

Extruder manufacturer, trade name, model no., serial no., Date of Manufacture

Date of Installation

Maximum rated capacity (lb/hour), Diameter of barrel Length of heated portion of extruder (ft), Number of heat zones and rating (Kw)

Mode of quenching (water/air/none/other), Mode of venting (atmosphere/vacuum - inches of water)

Method of feed conveyance

Type of product manufactured, particle size, shape, density

Type of material processed - manufacture, trade name, code no., amount used (lb/hr), content of free monomer (%),

particle size, shape, density, MSDS's.

Types of additives used (eg. plasticizer, blowing agent), manufacturer, trade name, code number, amount used (parts/100 parts resin), particle size, shape, density, percent in feed, percent in product, MSDS's.

Operating parameters, methods for determining how equipment is operating, determining production capabilities, factors which influence production

Method of cleaning parts and equipment (e.g., sandblasting, burn-off, clean furnace, chemical removal)

MISCELLANEOUS INDUSTRIAL PROCESSES

Equipment Manufacturer, Model No., Serial No., Date of Manufacture

Date of Installation

Maximum Production Rate, tons/hour, widgets/hour, etc.)

Indication of potential emission points

Exhaust system description

Description of material inputs (identification of chemical products and their usages, MSDS's)

Operating parameters: (methods for determining how equipment is operating, determining production capabilities, factors which influence production)

Exhaust system description: (exhaust temperatures and pressures, moisture content, constituents of the exhaust stream, airflow rates)

Method of cleaning parts and equipment (e.g., sandblasting, burn-off, clean furnace, chemical removal)

ATTACHMENT B

AIR POLLUTION CONTROL EQUIPMENT

Attach a description of the air pollution control system. This attachment must describe the basic methods applied to remove air contaminants as well as the following details:

- (1) Data and calculations used in the sizing and selection of the control equipment.
- (2) Data and calculations used to determine the control efficiency.
- (3) If the control equipment is standard and commercially available off the shelf, specify the manufacturer, type, model, and capacity of the equipment. Manufacturers literature would be helpful.
- (4) If the control system consists of other than standard equipment, provide a sketch of the control equipment.
- (5) Describe the means of disposal of any air contaminants which are collected by the control equipment.
- (6) Show any bypass of the control equipment and specify when and under what conditions the bypass will be used. The APCD may deny permission for the installation of a bypass.
- (7) Describe the procedure to be used for maintaining and operating the unit, including schedule.
- (8) Include fixed and indirect cost estimates.

ADDITIONAL DATA NEEDED FOR SPECIFIC CONTROL DEVICES

SCRUBBER
<p>Purpose of device: acid gas or particulate control Type of scrubber (e.g., venturi, bubble plate, etc.) Gas flow rate before the scrubber in cubic feet per minute (cfm) Liquid flow rate in gallons per minute (gpm) Scrubbing liquid used pH of scrubbing liquid Chemical additives used (if any) and amounts (provide Material Safety Data Sheets for each chemical product) Scrubbing liquid, once through or recirculated Plan for disposal of scrubbing liquid (municipal sewer plant, onsite, etc.) Sketch of device Pressure drop across scrubber in inches of water (inches of water column) Demister type and dimensions</p> <p><i>*NOTE*</i> For packed scrubber indicate type of packing and dimensions of packed bed</p>

CYCLONE/MULTICYCLONE
<p>Wet or dry cyclone Particle size distribution and density of contaminant Pressure drop in inches of water column Cyclone inlet temperature in °F Dimensions of cyclone Is the system equipped with an airlock?</p>

FILTER PADS

Type of filter
Dimensions of filter bank
Control efficiency relative to a specific particle size
Pressure drop in inches of water column

ADSORPTION

Adsorbent and amount to be used
Adsorbent capacity for specific contaminant (i.e., lbs. contaminant/lbs. adsorbent)
Collection efficiency of adsorbent for contaminant being controlled
Operating pressures (psig)
Operating temperatures (°F)
Dimensions of bed
Gas flow rate through bed in cfm
Method of measuring activity
Method and schedule of reactivation (if applicable)
Method of disposal of desorbate

CONDENSER

Type of condenser
Entrance and exit temperatures of gas stream in °F
Type of cooling medium
Flow of cooling liquid in gallons per minute
Area of cooling surface in square feet (sq. ft.)

ELECTROSTATIC PRECIPITATOR

Evidence that contaminant is liquid or solid and not vapor.
Are contaminants heated or cooled between source and precipitator?
Type of unit (e.g., 1 or 2 stage, tube, plate)
Method of cleaning (e.g., rapping, gravity, wash off)
Capacity in cubic feet per minute
% Moisture in gas stream
Temperature of inlet stream in °F
Collecting surface area in sq. ft.
Apparent migration velocity (precipitation rate)
Corona power
Resistivity of particles

FABRIC FILTER

Number and dimensions of bags
Total cloth filtering area
Maximum rated air flow rate in actual cubic feet per minute
Type of bag fabric
Fabric weight, weave and finish of bags
Air to cloth ratio
Method of cleaning (if pulse jet indicate pressure in psi)
Operating pressure drop in inches of water column
Inlet and outlet temperature (°F)
Description of access to filter bags for maintenance
Is the unit capable of fluorescent powder testing (e.g., visolite)?
Is the system equipped with an airlock?

ABSORPTION

Type (e.g., spray dryer, packed, sieve plate, bubble plate)
Dimensions of Unit
Liquid used
Amount of liquid used in gallons per minute
If spray dryer type - inlet and outlet temperatures (°F)
 slurry concentration (%)
 slurry feedrate (gallons per minute)
 dilution water flow rate (gallons per minute)
 atomizing air pressure (psi)
 control mode (automatic/manual)
Gas flow rate through unit in standard cubic feet per minute
Method of rich liquid disposal (stripping tower, neutralization, other)
Number of transfer units (NOG); Height of transfer units (HOG)
Identify surfactants

COMPRESSION, REFRIGERATION

Equilibrium temperature of condenser in °F
Composition of feed vapor
Composition of recovered liquid and/or vapor and quantity of each
Number of equilibrium stages

INCINERATION

Burner maximum rated heat input in million Btus per hour
Fuel type
Maximum fuel flow rate in gallons per minute or cubic feet per minute
Maximum incineration temperature in °F
Residence time in seconds
Exit temperature of the gas stream in °F

SELECTIVE CATALYTIC REDUCTION

Type and characteristics (physical properties) of catalyst: honeycomb (hexagonal), honeycomb (square), honeycomb (triangle), plate
Location of catalyst
Catalyst parameters (open cross-sectional area, length, cell density, volume of catalyst, surface area of catalyst)
Operating conditions (inlet and outlet NO_x concentrations, ppmv, gas flow rate, inlet and outlet temperature, °F, pressure drop, inches of water)
Catalyst life and catalyst replacement schedule ammonia injection system (detail of ammonia injection grid, ammonia flow, nozzle size, ammonia injection grid pressure, duct pressure)
Maintenance procedures for the ammonia injection grid system
Description of system to control ammonia slip and optimize NO_x control

WATER/STEAM INJECTION

Maximum water injection rate, gallons per minute
Maximum fuel injection rate, gallons per minute
Maximum and minimum water to fuel ratio and corresponding carbon monoxide and nitrogen oxides emissions (ppmv corrected to 15% O₂)

SELECTIVE NON-CATALYTIC REDUCTION

Description of injection system (number and location of injection points)
Operating temperature at point of injection
Solution to be injection (urea, aqueous ammonia, other)
Concentration of solution to be injected
Maintenance procedures for the injection system
Description of system to control ammonia slip and optimize NO_x control